

**Model VG400 - Indirect Fired Gas Heater
Specifications**



| | |
|-------------------------|--------------------------------------|
| Input | 400,000 BTU/Hr |
| Fuel | Vapor Propane/Natural Gas |
| Gas Consumption | 4.4 GPH Propane/400 CFH NG |
| Gas Connection | 3/4" FNPT |
| Electrical | 120 Volts 20 amp circuit |
| Fan | 2,100 CFM 1/2" SP |
| Thermostat | Standard On/Off |
| Temp Rise | 200°F @ 0°F Ambient |
| Rated Efficiency | 80% |
| Shipping Dim | 60"L x 24"W x 45"H |
| Duct Size | 12" Dia. (up to 50' straight) |
| Weight | 400 lbs. |

| | | |
|-------------------|-----------------------|-----------------|
| Gas Supply | Inlet Pressure | |
| | Max W.C. | Min W.C. |
| Propane | 14" | 9" |
| Natural | 14" | 9" |

- Versatility of dual fuel - natural gas & propane**
- Remote thermostat**
- Wheels for easy portability**
- Long lasting stainless steel combustion chamber**
- "Whisper quiet" centrifugal fan**
- Ideal for greenhouses and large premises**
- Ductable to 200 ft.**
- 100% dry heat, clean of combustion by-products**