## Model VG700 - Indirect Fired Gas Heater Specifications



Input 700,000 BTU/Hr

Fuel # 1/2 Diesel/Vapor Propane/Natural Gas

Gas Consumption 5.5 GPH Propane/500 CFH NG

Gas Connection 1" FNPT

Electrical 240 Volts 15 amp circuit

Fan 7,420CFM 2"W.C. SP/6,475 CFM 2.05" W.C. SP

Thermostat Standard On/Off

Temp Rise 120°F/72°F @ 0°F Ambient

Rated Efficiency 85%/80%

Shipping Dim 79Lx29Wx51H/90"L x 40"W x 60"H

Duct Size 24"/21" (up to 200' straight)

Weight 550lbs/650 lbs.

| Gas Supply | Inlet Pressure |          | Manifold Pressure |
|------------|----------------|----------|-------------------|
|            | Max W.C.       | Min W.C. | w.c.              |
| Propane    | 14"            | 9"       | 3.6"              |
| Natural    | 14"            | 9"       | 6.1"              |

Versatility of dual fuel - natural gas & propane

**Remote thermostat** 

Wheels for easy portability

Long lasting stainless steel combustion chamber

"Whisper quiet" centrifugal fan

Ideal for greenhouses and large premises

Ductable to 200 ft.

100% dry heat, clean of combustion by-products